

```

//
// AddViewController.h
// Catalogue
//
// Created by kcfancher on 8/6/12.
// Copyright (c) 2012 kcfancher. All rights reserved.
//

#import <UIKit/UIKit.h>

// Tells the compiler to ignore the error messages caused
// by not recognizing AddViewController or Item in
// our protocol methods
@class AddViewController;
@class Item;

// Create a protocol for our delegate
@protocol AddViewControllerDelegate <NSObject>
// Define to methods to be called on our delegate
- (void)addViewController:(AddViewController *)addVC didSaveItem:(Item *)newItem;
- (void)addViewControllerDidCancel:(AddViewController *)addVC;
@end

@interface AddViewController : UITableViewController
- (IBAction)done:(UIBarButtonItem *)sender;

- (IBAction)cancel:(UIBarButtonItem *)sender;

@property (weak, nonatomic) IBOutlet UITextField *nameTextField;
@property (weak, nonatomic) IBOutlet UITextField *creatorTextField;
@property (weak, nonatomic) IBOutlet UITextField *priceTextField;
@property (weak, nonatomic) IBOutlet UITextField *idTextField;
@property (weak, nonatomic) IBOutlet UISegmentedControl *itemTypeSelector;

// Define a delegate property
// Delegate properties must always be weak and of type id
// with the Delegate protocol name specified in <>
@property (weak, nonatomic) id <AddViewControllerDelegate> delegate;

@end

```